

# ARTEDOMUS

STONE • TILE • MOSAIC • BATHWARE • TIMBER FLOORING



## INSTALLATION INSTRUCTIONS

### How to lay Zellige tiles

Open several boxes and randomly mix Zellige tiles with multiple tones and textures of the colour selected.

The surface should be well prepared and levelled before placing the Zellige.

Evenly apply flexible adhesive for ceramics on the surface and on the back of the tile.

Alternatively fix the Zellige with silicone.

Position the tiles by hand, leaving no joint (edge to edge) without using tile spacers, looking for the harmony of the whole

Once the tile are placed, spread very liquid grout cement over the surface, with a rubber spatula, insisting on filling the spaces between the tiles. Dyed grout may be used.

After a brief drying, carefully remove the excess cement with a damp sponge. Remove the remaining joint cement with a dry cloth carefully rubbing by hand.

Zellige tiles can be easily cut in an angle with a diamond disc and water.

### Zellige on floors

Zellige tiles can be laid on floors, in light traffic areas where the tiles would not be exposed to impacts.

Particular attention should be paid to the application of the adhesive on the floor and back of the tiles to ensure perfect bonding between Zellige tile pieces and concrete slab.

### Zellige in showers and swimming pools

Surface in direct contact with water: Swimming pools, shower floors and walls, fountains, worktops. Ensure the surface laid on is waterproof, stable and rigid prior to the installation of the Zellige tiles. Use adhesive cement and grout fit for these wet spaces.

1118 Great North Road Point Chevalier, Auckland

+64 9 361 1567

[www.artedomus.co.nz](http://www.artedomus.co.nz)



# ARTEDOMUS

STONE • TILE • MOSAIC • BATHWARE • TIMBER FLOORING

## Zellige maintenance

Glazed Zellige tiles do not require specific maintenance, they may be cleaned like any other types of glazed ceramic tiles.

## Important notes regarding « Metallic Zellige »

"Metallic colour" Zellige are clay tiles covered with a metallic film and protected by a synthetic varnish. The metallic tiles must be carefully installed, without hammering and avoiding abrasive situations, to limit the risk of posterior oxidation. "Metallic colour" tiles cannot be cut on-site. Mosaic del Sur may manufacture upon request special parts and cut to measure pieces in metallic finish according to your requirements.

Neutral pH products are recommended for cleaning.



1118 Great North Road Point Chevalier, Auckland

+64 9 361 1567

[www.artedomus.co.nz](http://www.artedomus.co.nz)



# ARTEDOMUS

STONE • TILE • MOSAIC • BATHWARE • TIMBER FLOORING

1118 Great North Road Point Chevalier, Auckland

+64 9 361 1567

[www.artedomus.co.nz](http://www.artedomus.co.nz)

